

### Warning



## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Trade name	: Nitrogen (refrigerated); Gourmet N – E 941 ; Pharmaline N
SDS no	: RS-N2-089B
Other means of identification	
CAS no.	: 7727-37-9
EC no.	: 231-783-9
Index no.	: ---
REACH no.	: Listed in Annex IV / V REACH, exempted from registration.
Chemical formula	: N <sub>2</sub>

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	: Industrial and professional uses. Perform risk assessment prior to use. Test gas / Calibration gas. Laboratory use. Purge gas, diluting gas, inerting gas. Shield gas for welding processes. Use for manufacture of electronic / photovoltaic components. Food applications. Medical applications.
Uses advised against	: Consumer use. Uses other than those listed above are not supported, contact your supplier for more information on other uses. Attention: These products must not be applied to humans or animals unless they are expressly designated as medical or medicinal gases!

### 1.3. Details of the supplier of the safety data sheet

Messer Tehnogas AD Beograd  
Banjicki put , 62  
RS- 11090 Belgrade, Serbia  
T +381 11 35 37 200 - F +381 11 35 37 291  
[postoffice@messer.rs](mailto:postoffice@messer.rs) - [www.messer.rs](http://www.messer.rs)

### 1.4. Emergency telephone number

Emergency telephone number	: Poison Control Center, VMA Crnotravska 17, Belgrade Serbia Tel. : +381(0) 11 360 8440 (24h)
----------------------------	---

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Physical hazards      Gases under pressure : Refrigerated liquefied gas      H281

### 2.2. Label elements

#### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS04

Signal word (CLP)	: Warning
Hazard statements (CLP)	: H281 - Contains refrigerated gas; may cause cryogenic burns or injury.

Precautionary statements (CLP)

- Prevention : P282 - Wear cold insulating gloves and either face shield or eye protection.
- Response : P336 + P315 - Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.
- Storage : P403 - Store in a well-ventilated place.

**2.3. Other hazards**

Asphyxiant in high concentrations.  
Not classified as PBT or vPvB.  
The substance/mixture has no endocrine disrupting properties.

**SECTION 3: Composition/information on ingredients**

**3.1. Substances**

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP] ATE, EUH-statements, M-Factors
Nitrogen (refrigerated)	CAS no.: 7727-37-9 EC no.: 231-783-9 Index no.: --- REACH no.: *1	100	Press. Gas (Ref. Liq.), H281

Contains no other components or impurities which will influence the classification of the product.

\*1: Listed in Annex IV / V REACH, exempted from registration.

\*3: Registration not required: Substance manufactured or imported < 1t/y.

**3.2. Mixtures**

Not applicable

**SECTION 4: First aid measures**

**4.1. Description of first aid measures**

- Inhalation : Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Maintain an open airway. Call a doctor. Perform cardiopulmonary resuscitation if breathing stopped.
- Skin contact : Carefully remove contaminated clothing. In case of frostbite spray with water for at least 15 minutes. Do not use hot water! Apply a sterile dressing. Obtain medical assistance.
- Eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes. Remove any contact lenses. Obtain medical assistance.
- Ingestion : Ingestion is not considered a potential route of exposure.

**4.2. Most important symptoms and effects, both acute and delayed**

In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation. See section 11.

**4.3. Indication of any immediate medical attention and special treatment needed**

Take first aid measures. Loosen tight clothing, such as a collar, tie or belt. Place the unconscious person in a lateral position. Seek medical attention.

**SECTION 5: Firefighting measures**

**5.1. Extinguishing media**

- Suitable extinguishing media : Water spray or fog.  
Product does not burn, use fire control measures appropriate for the surrounding fire.
- Unsuitable extinguishing media : Do not use water jet to extinguish.

**5.2. Special hazards arising from the substance or mixture**

- Specific hazards : Exposure to fire may cause containers to rupture/explode.
- Hazardous combustion products : None.

### 5.3. Advice for firefighters

Specific methods

- : Use fire control measures appropriate for the surrounding fire. Exposure to fire and heat radiation may cause gas receptacles to rupture. Cool endangered receptacles with water spray jet from a protected position. Prevent water used in emergency cases from entering sewers and drainage systems.
- If possible, stop flow of product.
- Use water spray or fog to knock down fire fumes if possible.
- If leaking do not spray water onto container. Water surrounding area (from protected position) to contain fire.
- Move containers away from the fire area if this can be done without risk.

Special protective equipment for fire fighters

- : In confined space use self-contained breathing apparatus.
- Standard protective clothing and equipment (Self Contained Breathing Apparatus) for fire fighters.
- Standard EN 469 - Protective clothing for firefighters.
- Standard EN 659 - Protective gloves for firefighters.
- Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

- : Act in accordance with local emergency plan. Try to stop release.
- Evacuate area. Ensure adequate air ventilation.
- Use protective clothing. Stay upwind.
- Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous.
- See section 8 of the SDS for more information on personal protective equipment.

For emergency responders

- : Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe. Oxygen detectors should be used when asphyxiating gases may be released.
- See section 5.3 of the SDS for more information.

### 6.2. Environmental precautions

- Try to stop release.
- Liquid spillages can cause embrittlement of structural materials.

### 6.3. Methods and material for containment and cleaning up

- Ventilate area.

### 6.4. Reference to other sections

- See also sections 8 and 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Safe use of the product

- : The product must be handled in accordance with good industrial hygiene and safety procedures.
- Do not eat, drink or smoke while working with the product.
- Wash hands after use.
- Wear personal protective equipment (See section 8).
- Only experienced and properly instructed persons should handle gases under pressure.
- Consider pressure relief device(s) in gas installations.
- Ensure the complete gas system was (or is regularly) checked for leaks before use.
- Use only properly specified equipment which is suitable for this product, its supply pressure and temperature.
- Contact your gas supplier if in doubt.
- Avoid suck back of water, acid and alkalis.
- Do not breathe gas.
- Avoid release of product into work area.

### Safe handling of the gas receptacle

- : Refer to supplier's container handling instructions.
- Protect containers from physical damage; do not drag, roll, slide or drop.
- When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders.
- Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use.
- If the protection cap is too tight, remove it with adjustable wrench.
- Never insert sharp objects into the cavities of the cap, this can lead to damage to the valve and leakage. Open valve slowly to avoid pressure shock.
- If user experiences any difficulty operating valve discontinue use and contact supplier.
- Never attempt to repair or modify container valves or safety relief devices.
- Damaged valves should be reported immediately to the supplier.
- Keep container valve outlets clean and free from contaminants particularly oil and water.
- Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment.
- Close container valve after each use and when empty, even if still connected to equipment.
- Never attempt to transfer gases from one cylinder/container to another.
- Never use direct flame or electrical heating devices to raise the pressure of a container.
- Do not allow backfeed into the container. Suck back of water into the container must be prevented.
- Do not remove or deface labels provided by the supplier for the identification of the content of the container.

### 7.2. Conditions for safe storage, including any incompatibilities

- Observe all regulations and local requirements regarding storage of containers.
- Containers should not be stored in conditions likely to encourage corrosion.
- Container valve guards or caps should be in place.
- Containers should be stored in the vertical position and properly secured to prevent them from falling over.
- Stored containers should be periodically checked for general condition and leakage.
- Keep container below 50°C in a well ventilated place.
- Store containers in location free from fire risk and away from sources of heat and ignition.
- Keep away from combustible materials.
- For more guidance on the safe storage of liquid oxygen, liquid nitrogen or liquid argon, refer to EIGA Doc.224 "Static Vacuum Insulated Cryogenic Vessels Operation and Inspection", downloadable at <http://www.eiga.eu> and consult your supplier.

### 7.3. Specific end use(s)

None.

## **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters

- OEL (Occupational Exposure Limits) : None available.
- DNEL (Derived-No Effect Level) : None available.
- PNEC (Predicted No-Effect Concentration) : None available.

### 8.2. Exposure controls

#### **8.2.1. Appropriate engineering controls**

- Provide adequate general and local exhaust ventilation.
- Systems under pressure should be regularly checked for leakages.
- Oxygen detectors should be used when asphyxiating gases may be released.
- Consider the use of a work permit system e.g. for maintenance activities.

#### **8.2.2. Individual protection measures, e.g. personal protective equipment**

- A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk.
- The following recommendations should be considered: PPE compliant to the recommended EN/ISO standards should be selected.

- Eye/face protection : Wear goggles and a face shield when transfilling or breaking transfer connections. Standard EN 166 - Personal eye-protection - specifications.
- Skin protection : Wear working gloves when handling gas containers. Standard EN 388 - Protective gloves against mechanical risks, [performance level 1 or higher](#). Recommended types include wrist gloves from leather or synthetic material with equivalent performance, fabric gloves, fabric gloves with leather palms. Wear cold insulating gloves when transfilling or breaking transfer connections. Standard EN 511 - Cold insulating gloves, [performance level 1 or higher](#). Recommended types include insulated gauntlets or gloves specifically selected to prevent liquid penetration and ingress of cryogenic liquids and to provide mechanical resistance.
- Hand protection
- Other : Wear safety shoes while handling containers. Standard EN ISO 20345 - Personal protective equipment - Safety footwear.
- Respiratory protection : Self contained breathing apparatus (SCBA) or positive pressure airline with mask are to be used in oxygen-deficient atmospheres. Self contained breathing apparatus is recommended, where unknown exposure may be expected, e.g. during maintenance activities on installation systems. Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask.
- Thermal hazards : None in addition to the above sections.

**8.2.3. Environmental exposure controls**

None necessary.

**SECTION 9: Physical and chemical properties**

**9.1. Information on basic physical and chemical properties**

Appearance	
- Physical state at 20°C / 101.3kPa	: Gas.
- Colour	: Colourless liquid.
Odour	: Odourless.
Melting point / Freezing point	: -210 °C
Boiling point	: -196 °C
Flammability	: Non flammable.
Lower explosion limit	: Not applicable.
Upper explosion limit	: Not applicable.
Flash point	: Not applicable for gases and gas mixtures.
Auto-ignition temperature	: Non flammable.
Decomposition temperature	: Not applicable.
pH	: Not applicable for gases and gas mixtures.
Viscosity, kinematic	: No reliable data available.
Water solubility [20°C]	: 20 mg/l
Partition coefficient n-octanol/water (Log Kow)	: Not applicable for inorganic products.
Vapour pressure [20°C]	: Not applicable.
Vapour pressure [50°C]	: Not applicable.
Density and/or relative density	: Not applicable for gases and gas mixtures.
Relative vapour density (air=1)	: 0.97
Particle characteristics	: Not applicable for gases and gas mixtures. Nanoforms are not relevant for gases and gas mixtures.

**9.2. Other information**

**9.2.1. Information with regard to physical hazard classes**

Explosion limits	: Not known.
Oxidising properties	: No oxidising properties.
Critical temperature [°C]	: -147 °C

**9.2.2. Other safety characteristics**

Molar mass	: 28 g/mol
------------	------------

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

No reactivity hazard other than the effects described in sub-sections below.

#### 10.2. Chemical stability

Stable under normal conditions.

#### 10.3. Possibility of hazardous reactions

None.

#### 10.4. Conditions to avoid

Avoid moisture in installation systems.

#### 10.5. Incompatible materials

For additional information on compatibility refer to ISO 11114.  
Materials such as carbon steel, low alloy carbon steel and plastic become brittle at low temperatures and are subject to failure. Use appropriate materials compatible with the cryogenic conditions present in refrigerated liquefied gas systems.

#### 10.6. Hazardous decomposition products

None.

### SECTION 11: Toxicological information

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity	: No known toxicological effects from this product.
Skin corrosion/irritation	: No known effects from this product.
Serious eye damage/irritation	: No known effects from this product.
Respiratory or skin sensitisation	: No known effects from this product.
Germ cell mutagenicity	: No known effects from this product.
Carcinogenicity	: No known effects from this product.
Toxic for reproduction : Fertility	: No known effects from this product.
Toxic for reproduction : unborn child	: No known effects from this product.
STOT-single exposure	: No known effects from this product.
STOT-repeated exposure	: No known effects from this product.
Aspiration hazard	: Not applicable for gases and gas mixtures.

#### 11.2. Information on other hazards

Other information : The substance/mixture has no endocrine disrupting properties.

### SECTION 12: Ecological information

#### 12.1. Toxicity

Assessment	: No ecological damage caused by this product.
EC50 48h - Daphnia magna [mg/l]	: No data available.
EC50 72h - Algae [mg/l]	: No data available.
LC50 96 h - Fish [mg/l]	: No data available.

#### 12.2. Persistence and degradability

Assessment : No ecological damage caused by this product.

#### 12.3. Bioaccumulative potential

Assessment : No ecological damage caused by this product.

#### 12.4. Mobility in soil

Assessment : No ecological damage caused by this product.

**12.5. Results of PBT and vPvB assessment**

Assessment : Not classified as PBT or vPvB.

**12.6. Endocrine disrupting properties**

Assessment : The substance/mixture has no endocrine disrupting properties.

**12.7. Other adverse effects**

Other adverse effects : Can cause frost damage to vegetation.  
Effect on the ozone layer : No effect on the ozone layer.  
Effect on global warming : None.

**SECTION 13: Disposal considerations**

**13.1. Waste treatment methods**

Do not discharge into any place where its accumulation could be dangerous.  
May be vented to atmosphere in a well ventilated place.  
Return unused product in original container to supplier.  
[Refer to the EIGA code of practice Doc.30/21 "Disposal of Gases", downloadable at http://www.eiga.eu for more guidance on suitable disposal methods.](http://www.eiga.eu)

List of hazardous waste codes (from Commission Decision 2000/532/EC as amended) : 16 05 05 : Gases in pressure containers other than those mentioned in 16 05 04\*.

**13.2. Additional information**

External treatment and disposal of waste should comply with applicable local and/or national regulations.

**SECTION 14: Transport information**

**14.1. UN number or ID number**

In accordance with ADR / RID / IMDG / IATA / ADN  
UN-No. : 1977

**14.2. UN proper shipping name**

**Transport by road/rail/inland waterways (ADR/RID/ADN)** : NITROGEN, REFRIGERATED LIQUID  
**Transport by air (ICAO-TI / IATA-DGR)** : Nitrogen, refrigerated liquid  
**Transport by sea (IMDG)** : NITROGEN, REFRIGERATED LIQUID

**14.3. Transport hazard class(es)**

Labelling :



2.2 : Non flammable, non-toxic gases.

**Transport by road/rail/inland waterways (ADR/RID/ADN)**

Class : 2  
Classification code : 3A  
Hazard identification number : 22  
Tunnel Restriction : C/E - Tank carriage : Passage forbidden through tunnels of category C, D and E. Other carriage : Passage forbidden through tunnels of category E

**Transport by air (ICAO-TI / IATA-DGR)**

Class / Div. (Sub. risk(s)) : 2.2

**Transport by sea (IMDG)**

Class / Div. (Sub. risk(s)) : 2.2  
Emergency Schedule (EmS) - Fire : F-C  
Emergency Schedule (EmS) - Spillage : S-V





**SECTION 16: Other information**

Revised Safety Data Sheet in accordance with commission regulation (EU) No 2020/878.  
In Section 5, the Safety Data Sheet is supplemented with information about special hazards arising from the substance or mixture.  
In Section 6, the Safety Data Sheet is supplemented with information about personal precautions, protective equipment and emergency procedures.  
In Section 7, the Safety Data Sheet is supplemented with information about conditions for safe storage, including any incompatibilities.  
In Section 8, the Safety Data Sheet is supplemented with information about exposure control and personal protection.  
In Section 13, the Safety Data Sheet is supplemented with information about waste treatment methods.  
In Section 15, the Safety Data Sheet is supplemented with regulatory information.

Indication of changes : ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road  
ATE - Acute Toxicity Estimate  
CAS - Chemical Abstract Service number  
CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008  
CSA - Chemical Safety Assessment  
DNEL - Derived No Effect Levels  
EINECS - European Inventory of Existing Commercial Chemical Substances  
EC- European Community number  
EIGA - European Industrial Gases Association  
EN - European Standard  
IATA - International Air Transport Association  
ICAO - International Civil Aviation Organization  
IMDG code - International Maritime Dangerous Goods  
IMO - International Maritime Organization  
LC50 - Lethal Concentration to 50 % of a test population  
LD50 - Lethal Dose 50%  
LEL - Lower Explosive Limit  
OEL - Occupational exposure limits  
PBT - Persistent, Bioaccumulative and Toxic  
PNEC - Predicted No Effect Concentration  
PPE - Personal Protection Equipment  
REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006  
RID - Regulations concerning the International Carriage of Dangerous Goods by Rail  
RMM - Risk Management Measures  
STOT- RE - Specific Target Organ Toxicity - Repeated Exposure  
STOT- SE - Specific Target Organ Toxicity - Single Exposure  
STEL - Short Term Exposure Limit  
TWA –8-hour total weight average  
UEL - Upper explosive limit  
UFI - Unique Formula Identifier  
UN - United Nations  
vPvB - Very Persistent and Very Bioaccumulative  
WGK - Water Hazard Class

Abbreviations and acronyms : The hazard of asphyxiation is often overlooked and must be stressed during operator training. For more guidance, refer to EIGA SL 01 "Dangers of Asphyxiation", downloadable at <http://www.eiga.eu>

Further information : Classification in accordance with the procedures and calculation methods of Regulation (EC) 1272/2008 (CLP). Key literature references and sources of data are maintained in EIGA doc 169 : 'Classification and Labelling Guide', downloadable at <http://www.eiga.eu>

Full text of H- and EUH-statements	
H281	Contains refrigerated gas; may cause cryogenic burns or injury.
Press. Gas (Ref. Liq.)	Gases under pressure : Refrigerated liquefied gas

### DISCLAIMER OF LIABILITY

: Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out.  
Details given in this document are believed to be correct at the time of going to press.  
Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.

**End of document**